

ŠIAULIŲ AERODROMO NAUDOJIMO MINIMUMAI

OPERATING MINIMA FOR ŠIAULIAI AERODROME

Artėjimo tūpti procedūra <i>Approach procedure</i>		Orlaivio greičio kategorija/ <i>Aircraft speed category</i>			
		A	B	C	D
		DA(H), MDA(H) / RVR (FALS ¹ ir/ <i>and</i> NALS ²)			
RWY 14L	ILS CAT I	647' (200') R550 R1200	647' (200') R550 R1200	647' (200') R550 R1200	647' (200') R550 R1200
	LOC	830' (380') R1000 R1500	830' (380') R1000 R1500	830' (380') R1000 R1700	830' (380') R1000 R1700
	LOC (kai negautas SDF/ <i>when SDF not received</i>)	1000' (550') R2000 R2700	1000' (550') R2000 R2700	1000' (550') R2200 R2900	1000' (550') R2200 R2900
	LNAV	990' (540') R1500 R1500	990' (540') R1500 R1500	990' (540') R1700 R2400	990' (540') R1700 R2400
	VOR	840' (390') R1100 R1500	840' (390') R1100 R1500	840' (390') R1100 R1800	840' (390') R1100 R1800
	VOR (kai negautas SDF/ <i>when SDF not received</i>)	1000' (550') R2000 R2700	1000' (550') R2000 R2700	1000' (550') R2200 R2900	1000' (550') R2200 R2900
RWY 32R	ILS CAT I	641' (200') R550 R1200	641' (200') R550 R1200	641' (200') R550 R1200	641' (200') R550 R1200
	LOC	760' (320') R750 R1400	760' (320') R750 R1400	760' (320') R750 R1400	760' (320') R750 R1400
	LNAV	800' (350') R900 R1500	800' (350') R900 R1500	800' (350') R900 R1600	800' (350') R900 R1600
	VOR	930' (480') R1700 R2600	930' (480') R1700 R2600	930' (480') R1900 R2600	930' (480') R1900 R2600
Artėjimas tūpti ratu <i>Circling Approach</i>		880' (440') 1500 m	1160' (710') 2400 m	1260' (810') 3600 m	1260' (810') 3600 m

¹FALS – visa artėjimo tūpti apšvietimo sistema/*full approach lighting system*²NALS – artėjimo tūpti apšvietimo sistemos nebuvimas/*no approach lighting system*